

# DVR 4 Channel BNC 7104H

[www.avtechmurah.com](http://www.avtechmurah.com)



## FEATURES:

- Stand-Alone DVR, H.264 Compression
- Playback resolution: 4 x CIF
- Support capacity 2000GB
- High quality video Display : NTSC (720x480), PAL (704x576) real time display
- Multiple Recording/ Search Categories:Date/Time, Event, Manual, Schedule, alarm, motion detection
- Real time recording support: 120 Fps for NTSC at CIF image (100 Fps for PAL)
- 4ch Video recording at the same time
- Pentaplex: Live, Record, Playback, Back-up and Network at the same time
- Backup: CD-RW (Option: DVD-RW), USB 2.0 and NET backup supported
- PTZ camera control in local and remote area
- E-mail notification
- 3G support

## Network Viewer:

- Static, Dynamic IP and DDNS , Support Internet Explorer and special client software
- Remote Live Monitoring, file searching, Backup, Playback and PTZ camera control
- Remote Configuration, Firmware Upgrade and Event (Alarm, Motion) Notification
- Full duplex two way audio transmission

## Rear panel:

Items	Specifications
Model Name	DVR7104H
Compression Standard	H.264 (ASIC)
Resolution	Preview resolution : 704 x 576 ( PAL ) , 720 x 480 ( NTSC ) Playback resolution : 4 x CIF Frames : 1F/S ~ 30F/S (Adjustable)
Hard Disk	1 SATA Hard Disk interface
Video Signal	PAL (625Line, 50f/s) , NTSC (525Line, 60f/s)

Video Input	4 channel, BNC , 1.0V p-p/75Ω
Composite Video Output	1 channel, BNC, 1.0V p-p/75Ω
Monitor Video Output	1 channel, BNC, 1.0V p-p/75Ω
VGA Interface	1 VGA, Resolution: 800x600/60HZ, 1024x768/60HZ
Audio Input	No audio
Audio Output	No audio
Alarm Input	No alarm
Alarm Output	No alarm
Alarm Mode	Sensor Input, Motion Detection, Video Loss, Full Disk Space.
Network	Ethernet (10/100M ), LAN、 WAN and ADSL
Control Way	USB2.0 Mouse, Remote Control, Camera, RS485 x 1
Backup	USB2.0, CDRW, DVDRW and Network
Bit Rate	5 Levels : 120MB/H, 150MB/H, 250MB/H, 300MB/H, 500MB/H, 1~1000MB/H Self-defined
Password	Encrypted by 128-bit Numerical Digits with 2-Level Password Protection
Power Supply	DC12V 3.0A
Consumption	10W (Without HDD)
Working Environment	Temperature: +5°C~+50°C ; Humid : < 90%
Device Dimension	220 x 210 x 44 mm (W*D*H)
Weight	N.W: 2.5KG G.W: 2.8KG

[www.avtechmurah.com](http://www.avtechmurah.com)