



<b>Model</b>	<b>SM800A Series</b>
<b>Operation</b>	
<b>Lens</b>	Sony FCB-EX480
	¼ Inchi Sony CCD, 480 TVL, D/N, 0.01Lux, ICR function F=4.1-73.8mm, 18X Optical zoom, 12X digital zoom
<b>OSD menu</b>	Yes
<b>Preset position</b>	128
<b>Scan</b>	Auto scan and left-right limited scan, speed adjustable
<b>Patrol</b>	4 tracks, 16 preset per track, speed and dwell time changeable
<b>Pattern</b>	2
<b>Alarm</b>	Support 4 input, 2 output (Default not include)
<b>Address range</b>	0--255
<b>Communication</b>	RS485
<b>Baud rate</b>	2400/4800/9600/19200
<b>Protocol</b>	Pelco-P/D, or others customized
<b>Leisure action</b>	Home place/Scan/Patrol/Pattern
<b>Device title</b>	Display on/off
<b>P/T position</b>	Display on/off
<b>Temperature info</b>	Display on/off
<b>Mechanical</b>	
<b>Pan range</b>	0° --360° continuously
<b>Pan speed</b>	0.1--240°/s
<b>Tilt range</b>	0° ---90° auto flip on/off
<b>Tile speed</b>	0.1--240°/s
<b>Precision</b>	0.05°
<b>Housing</b>	Aluminum alloy, vandal proof housing
<b>Lighting proof</b>	With 4000V video, data and power lighting proof
<b>Alarm</b>	4 input, 2 output
<b>Water proof</b>	IP66
<b>Work temp</b>	0°C---40°C (with fan and heater, work temp. is -35 °C---70°C)
<b>Work humidity</b>	Max 95%
<b>Power</b>	DC12V input
<b>Installation</b>	Outdoor and indoor installation