



Model	SM800C Series
Operation	
Lens	Chinese ZMW30DN ¼ Inchi Sony CCD, 480 TVL, D/N, 0.01Lux, IR Sensitive 30X Optical Zoom
OSD menu	Yes
Preset position	128
Scan	Auto scan and left-right limited scan, speed adjustable
Patrol	4 tracks, 16 preset per track, speed and dwell time changeable
Pattern	2
Alarm	Support 4 input, 2 output (Default not include)
Address range	0--255
Communication	RS485
Baud rate	2400/4800/9600/19200
Protocol	Pelco-P/D, or others customized
Leisure action	Home place/Scan/Patrol/Pattern
Device title	Display on/off
P/T position	Display on/off
Temperature info	Display on/off
Mechanical	
Pan range	0° --360° continuously
Pan speed	0.1--240°/s
Tilt range	0° ---90° auto flip on/off
Tile speed	0.1--240°/s
Precision	0.05°
Housing	Aluminum alloy, vandal proof housing
Lighting proof	With 4000V video, data and power lighting proof
Alarm	4 input, 2 output
Water proof	IP66
Work temp	0°C---40°C (with fan and heater, work temp. is -35 °C---70°C)
Work humidity	Max 95%
Power	DC12V input
Installation	Outdoor and indoor installation