



<b>Model</b>	<b>SM810SD</b>
<b>Camera</b>	
<b>Signal mode</b>	PAL/NTSC
<b>Sensor</b>	1/4" Interline Transfer CCD
<b>Effective pixel (P/N)</b>	752 (H) x 582 (V) / 768 (H) x 494 (V)
<b>Resolution</b>	Color 500TVL, B/W 570TVL
<b>Illumination</b>	0.7Lux(Color), 0.02Lux (B/W), 50IRE
<b>Optical zoom</b>	10X
<b>Digital zoom</b>	10X
<b>Lens</b>	F1.8, f=3.8mm--38mm
<b>White balance</b>	Auto
<b>S/N ratio</b>	More than 50dB
<b>Operation</b>	
<b>OSD menu</b>	English
<b>Preset position</b>	128
<b>Swing</b>	8 Swing
<b>Tour</b>	4 Tours (20 action entities per tour)
<b>Pattern</b>	4 patterns
<b>Alarm</b>	Support 4 input (Default not include)
<b>Private masking</b>	4 Zone
<b>Address range</b>	0--255
<b>Communication</b>	RS485
<b>Baud rate</b>	2400/4800/9600/19200
<b>Protocol</b>	Pelco-P/D auto detected, or others customized
<b>Parking action</b>	Home place/Swing/Tour/Pattern
<b>Device title</b>	Display on/off
<b>P/T position</b>	Display on/off
<b>Temperature info</b>	Display on/off
<b>Mechanical</b>	
<b>Pan range</b>	0° --360° continuously